## Crushing Principles of Mechanical Crushing



Improving Processes. Instilling Expertise.









# Objective

Explain the interaction between rock material and crusher





#### Take home messages

- The Take Home Messages will address:
- Trouble Shooting
- Improve Yield
- Improve Performance




# Agenda

- Crusher Application
- Cone Crusher Operating Principle
- Crusher Capacity
- Crusher Operation
- Optimization and Crusher Performance Map
- Conclusions



#### **Crusher Selection**


#### Feed size





[Reduction Ratio]


#### **Crusher Selection**



Material Toughness (WI)



#### **Crusher Selection**






# **Cone Crusher**


- Why Cone Crusher?
- The cone crusher design concept is an effective and smart way of realizing compressive crushing
- Aggregate Production
- Mechanical Liberation of Valuable Minerals









QUARRY ACADEMY































# Crushing Zone Concave Mantle

#### Single Particle Breakage SPB




#### Inter Particle Breakage IPB






- In a cone crusher the stones are crushed with both SPB and IPB as the material moves down through the chamber.
- The relative amounts of IPB and SPB depends on factors like chamber design, crusher geometry, speed, css, eccentric throw, and others.






#### **Crusher Capacity**




**QUARRY** ACADEMY





#### **Crusher Capacity**






- As the market demand shifts can the crusher operation be modified?
- The crusher is likely to be installed for maximum production.
  Can it be changed to maximum efficiency?


- Understanding how breakage and capacity is effected by
  - Eccentric Throw
  - Speed
  - Closed Side Setting








• Running the crusher at different eccentric throws, CSS optimized






Running the crusher at different speeds

ACADEM




- Relation between CSS and Shape
  - The size where the best shape can be found is at CSS
  - It is very difficult for cubical stones larger then CSS to pass the chamber
  - Breakage of stones creates flaky particles. Smaller flaky stones will more easily find its way through the chamber






- Relation between Feed size and Shape
  - The greater reduction ratio the worse particle shape.
  - Inter particle breakage improves shape. When crushing a bed of material weaker particles will break first. Flaky or elongated particles are weaker then round.
  - Breaking round particles gives flaky material.




Particle size [mm]









- Who is control of your process performance?
- What tools have been provided to make the production efficient?
- Maximize crusher yield
  - Production of valuable products
  - Efficient production of current product demands
- Crusher Performance Map will help guide the crusher operator





- This method applies to other crushers where a control variable is available
- The crushers are the last size reduction stage in the value chain.
- Over crushing is common.
- The connection between crusher setting and yield is often unknown
- The rock cannot be repaired.
- We need to control the crusher carefully.



Analysis

Sampling



Planning

 Optimization of one parameter (CSS) can be done by sampling and analysis

- The invested time and lost production will quickly be repaid by increased productivity
- Combine product yield and economic aspects
- This can be done by taking samples and making the analysis in MS Excel




Analysis

Sampling

Planning

- Material from crusher is sampled
- Measure the capacity at each crusher settings. CSS will effect the final product capacity, especially in a closed circuit.
- Production of 4 valuable products
  - 0.08-0.16" (2-4 mm)
  - 0.16-0.32" (4-8 mm)
  - 0.32-0.64" (8-16 mm)
  - 0.64-0.87" (16-22 mm)
- By-product with no value
  - 0-0.08" (0-2 mm)





Planning

ACADEM

Sampling

Analysis

- Run the crusher at different settings
- Take at least one sample at each setting. (Multiple samples are often useful)
- Special Attention to Safety when taking samples!!
- Position of point were samples are taking.
- Ensure that the conveyor will not start by accident.




Sampling

Planning

Analysis


- Particle Size Distribution Plots
- If taking single samples on each CSS the risk of getting inconsistent results might make the graph look strange.
- Impossible to determine optimum setting by only using particle size distribution graphs







- If taking single samples on each CSS the risk of getting inconsistent results might make the graph look strange.
- Impossible to determine optimum setting by only using particle size distribution graphs



**Capacity and CSS** 




Analysis

Planning

- Combine the particle size distribution and capacity.
- Percentage of final product times the capacity gives the production capacity of each product.

Sampling

- Example 0.08"-0.16" mm at CSS 0.79":
  - Percentage of crusher production
  - 20% 11% = 9%
  - Crusher capacity
  - 193 tph
  - Total Production:
  - 193 tph x 9% = 17 tph








Sampling


Analysis

- Entering all the values into MS Excel makes this easy to get production capacities.
- Still difficult to determine the optimal setting





Analysis



• Use the price\* per ton for all products:

**Optimization** 

- 0-0.08": \$ 0 (by-product)
- 0.08-0.16": \$ 12.30
- 0.16-0.32": \$ 13.85
- 0.32-0.64": \$ 16.90
  - 0.64-0.87": \$ 10.80
- Make an income graph by combining prices with capacity



Planning



Sampling




Sampling

Analysis

Optimization


- What difference does it make?
- Running the crusher 0.08" off:
  - Decrease the profit by 58.5 \$/h
  - Running the crusher at 1600 hours per year: 58.5\*1600=\$93600



**Crusher Yield** 




#### **Crusher Performance Map**




# **Crusher Performance Map**

- The general idea:
  - Select a crusher where you think optimization will be beneficial
  - Make a plan for what you would like to test
    - CSS, Speed, Curtain Position...
  - Run a sampling campaign
    - Particle size distribution, shape, capacity
  - Do the analysis
    - Convert test results into values of performance
  - Find the sweet spot





#### **Crusher Performance Map**



QUARRY ACADEMY

#### Conclusions

Capacity is determined by the choke zone

By tuning the crusher operation production efficiency can be improved. Throw, Speed and Chamber Selection

The Particle Shape can be improved by moving the reduction to earlier stages in the plant and selecting correct CSS

Process Capacity and Crusher Capacity must correspond

The effort put in to optimization will repay itself quickly

The Crusher Performance Map can assist your operator with maintaining efficient production



www.quarryacademy.com



Improving Processes. Instilling Expertise.



